

Cable Management

TY-RAP® Cable Ties



Pull Strengths:

120 lbs

50 lbs

40 lbs

18 lbs

TY-RAP® Cable Tie Features

- Low-profile head - won't snag
- Easy to install, won't slip, mechanic's grip
- Stainless steel lock, maintains right tension
- Infinitely adjustable design, always the "right" size
- Smooth molded body, less stress-sensitive than notched type
- Ribbed and stippled back, won't slip on bundle
- Registered as Standard 1565
- Qualified under OPC 23190

TY-RAP® Standard Nylon 6/6



TY-RAP® Nylon 6/6 - Weather resistant*



Qty. 100 Part Number	Qty. 1000 Part Number	Government Designation	Max Tensile Strength	Max Bundle Diameter	Apprx. Length	Body Width
PW523M	PW23M	MS3367-4	18 lbs.	.625"	3.62"	.091"
PW5232M	PW232M	MS3367-4	18 lbs.	2.0"	8.0"	.091"
PW5234M	PW234M	MS3367-4	18 lbs.	4.0"	14.0"	.091"
PW524M	PW24M	MS3367-5	30 lbs.	1.125"	5.5"	.140"
PW5242M	PW242M	MS3367-5	30 lbs.	2.0"	8.19"	.140"
PW526M	PW26M	MS3367-5	30 lbs.	3.0"	11.1"	.140"
PW5244M	PW244M	MS3367-5	30 lbs.	4.0"	14.5"	.140"
PW525M	PW25M	MS3367-1	50 lbs.	1.75"	7.31"	.184"
PW5253M	PW253M	MS3367-7	50 lbs.	3.0"	11.4"	.184"
PW528M	PW28M	MS3367-2	50 lbs.	4.0"	14.2"	.184"
PW5272M	PW272M	MS3367-2	120 lbs.	2.0"	9.0"	.270"
PW527M	PW27M	MS3367-3	120 lbs.	3.5"	13.4"	.270"
PW5275M	PW275M	MS3367-3	120 lbs.	5.0"	18.0"	.270"
PW5277M	PW277M	MS3367-3	120 lbs.	7.0"	24.3"	.270"
PW529M	PW29M	MS3367-6	120 lbs.	9.0"	30.0"	.301"
PW53510M	PW3510M	MS3367-6	175 lbs.	10.0"	35.0"	.320"
PW54513M	PW4513M	MS3367-6	175 lbs.	13.0"	45.0"	.320"

Qty. 100 Part Number	Qty. 1000 Part Number	Government Designation	Max Tensile Strength	Max Bundle Diameter	Apprx. Length	Body Width
PW523MX	PW23MX	MS3367-4	18 lbs.	.625"	3.62"	.091"
PW5232MX	PW232MX	MS3367-4	18 lbs.	2.0"	8.0"	.091"
PW5234MX	PW234MX	MS3367-4	18 lbs.	4.0"	14.0"	.091"
PW524MX	PW24MX	MS3367-5	30 lbs.	1.125"	5.5"	.140"
PW5242MX	PW242MX	MS3367-5	30 lbs.	2.0"	8.19"	.140"
PW526MX	PW26MX	MS3367-5	30 lbs.	3.0"	11.1"	.140"
PW5244MX	PW244MX	MS3367-5	30 lbs.	4.0"	14.5"	.140"
PW525MX	PW25MX	MS3367-1	50 lbs.	1.75"	7.31"	.184"
PW5253MX	PW253MX	MS3367-7	50 lbs.	3.0"	11.4"	.184"
PW528MX	PW28MX	MS3367-2	50 lbs.	4.0"	14.2"	.184"
PW5272MX	PW272MX	MS3367-2	120 lbs.	2.0"	9.0"	.270"
PW527MX	PW27MX	MS3367-3	120 lbs.	3.5"	13.4"	.270"
PW5275MX	PW275MX	MS3367-3	120 lbs.	5.0"	18.0"	.270"
PW5277MX	PW277MX	MS3367-3	120 lbs.	7.0"	24.3"	.270"
PW529MX	PW29MX	MS3367-6	120 lbs.	9.0"	30.0"	.301"
PW53510MX	PW3510MX	MS3367-6	175 lbs.	10.0"	35.0"	.320"
PW54513MX	PW4513MX	MS3367-6	175 lbs.	13.0"	45.0"	.320"

*Continuous operating temperature 221°F to -40°F.

*Weather resistant cable ties are recommended for outdoor use. Added carbon black provides very good UV resistance and prolongs the life of the cable tie. Continuous operating temperature 221°F to -40°F.