

# Heat Shrink Tubing

HEAT SHRINK

## Precut Heat Shrink Tubing



Adhesive lined heat shrink in precut lengths of 3/4 and 1 1/2 inches.

3 to 1 shrink ratio is ideal for sealing battery cable ends against corrosion.



### Medium Duty Precut Adhesive Heat Shrink

| Part Number    | Color | Diameter | Length | Wire Sizes    |
|----------------|-------|----------|--------|---------------|
| HS-0375-RD-.75 | Red   | 3/8"     | 3/4"   | 8 – 1 AWG     |
| HS-0375-BK-.75 | Black | 3/8"     | 3/4"   | 8 – 1 AWG     |
| HS-0500-RD-1.5 | Red   | 1/2"     | 1 1/2" | 8 – 1 AWG     |
| HS-0500-BK-1.5 | Black | 1/2"     | 1 1/2" | 8 – 1 AWG     |
| HSRED          | Red   | 3/4"     | 1 1/2" | 8 – 1 AWG     |
| HSBLK          | Black | 3/4"     | 1 1/2" | 8 – 1 AWG     |
| HSRED-1        | Red   | 1"       | 1 1/2" | 1/0 – 4/0 AWG |
| HSBLK-1        | Black | 1"       | 1 1/2" | 1/0 – 4/0 AWG |

### Heavy Duty Precut Adhesive Heat Shrink

| Part Number | Color | Diameter | Length | Wire Sizes    |
|-------------|-------|----------|--------|---------------|
| HSREDHD     | Red   | 3/4"     | 1 1/2" | 8 – 1 AWG     |
| HSBLKHD     | Black | 3/4"     | 1 1/2" | 8 – 1 AWG     |
| HSREDHD-1   | Red   | 1"       | 1 1/2" | 1/0 – 4/0 AWG |
| HSBLKHD-1   | Black | 1"       | 1 1/2" | 1/0 – 4/0 AWG |

3 to 1  
shrink  
ratio



**RoHS**  
compliant



-55°C TO 110°C